

TR36

36W SWITCHING ADAPTER



SMIX POWER

3005 Avenida Simi, Simi Valley, CA 93063
TEL: (805) 582-2804 FAX: (805) 582-2308



Features

- Universal Input: 90 - 264Vac
- Continuous Short Circuit Protection
- Meets EN55022 Class "B", conducted
- High Efficiency, 85% Typical

Specifications

INPUT CHARACTERISTICS:

Voltage 90 - 264Vac
 Frequency 47 to 63Hz
 Inrush Current 50A Max. @ 264Vac
 Conducted EMI CISPR/FCC Class B
 Isolation Input to output -4,242Vdc
 Leakage Current 0.25mA max.

ENVIRONMENTAL CHARACTERISTICS:

Operating Temperature 0 - 40C
 Storage Temperature -20 - 85C

OUTPUT CHARACTERISTICS:

Holdup Time 8mS typ. @ 115Vac
 Short Circuit Protection Continuous
 Over Voltage Protection Option

MECHANICAL CHARACTERISTICS:

Dimensions 4.33x 1.96 x 0.78 Inches
 Weight 0.44 Pounds
 AC Inlet IEC320/C8

MODEL	OUTPUT VOLTAGE	OUTPUT CURRENT	RIPPLE & NOISE	VOLTAGE SETPOINT	LINE REGULATION	LOAD REGULATION
TR36A05	5 V	4.0 A	1%	+/- 2%	+/- 1%	+/- 6%
TR36A09	9 V	3.0 A	1%	+/- 2%	+/- 1%	+/- 5%
TR36A12	12 V	2.5 A	1%	+/- 2%	+/- 1%	+/- 5%
TR36A13	13.5 V	2.4 A	1%	+/- 2%	+/- 1%	+/- 5%
TR36A15	15 V	2.4 A	1%	+/- 2%	+/- 1%	+/- 3%
TR36A18	18 V	2.0 A	1%	+/- 2%	+/- 1%	+/- 2%
TR36A24	24 V	1.5 A	1%	+/- 2%	+/- 1%	+/- 2%
TR36A48	48 V	0.75A	1%	+/- 2%	+/- 1%	+/- 2%

NOTE:

1. Voltage setpoint at 60% load.
2. Add a 0.1uF ceramic capacitor and a 10uF E.L. capacitor to output for Ripple & Noise measurement @20MHz BW.
3. Line regulation measured from 100Vac to 240Vac, full load.
4. Load regulation measured from 60% to full load and from 60% to 20% load (80% +/- 40% full load)

Mechanical Specification

Unit: mm (in)

