

SMX POWER

3005 Avenida Simi, Simi Valley, CA 93063

TEL: (805) 582-2804 FAX: (805) 582-2308 www.smxpower.com



ATX-400PN

400 Watts ATX12V 2.01 Switching Power Supply

Features

- Complied with ATX12V 2.0 standard
- High efficiency and reliability
- Remote On/Off function
- Internal 12V DC fan included
- Noise Killer (Thermal fan speed control function)
- Low noise and ripple
- Complies with FCC part 15 subpart J Class B and CISPR 22 Class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL 60950, IEC 60950, TUV EN60950, NEMKO (CB Report)

Input Characteristics

Input Range: 100~132Vrms or 200~264Vrms, Manual selection

Frequency: 47~63Hz

Input Current: 8.5A (RMS) @115Vrms/60Hz, 5A (RMS) @ 230Vrms/50Hz

Inrush Current: 100A Max cold start, 120A Max warm start measured at 264Vrms/50Hz

Output Characteristics

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.5A	15.0A	30A	± 5%	± 1%	50mV P-P
+5V	1.0A	14.0A	28A	± 5%	± 1%	50mV P-P
+12V1DC	1.0A	7.0A	18A	± 5%	± 1%	120mV P-P
+12V2DC	1.0A	8.5A	18A	± 5%	± 1%	120mV P-P
-12V	0.0A	0.4A	0.5A	± 10%	± 2%	120mV P-P
+5Vsb	0.0A	1.0A	2.0 A	± 5%	± 1%	50mV P-P

*+3.3V and +5V total output not exceed 150W

When +3.3V is load to 30A, the +5V maximum load is 10A

When +3.3V is load to 3.0A, the +5V maximum load is 28A

*+12V1DC, 12V2DC total power not exceed 348W

*+3.3V, +5V, +12V1DC, and +12V2DC total output not exceed 385W

Specification

- **Temperature Range:** Operating 0° C ~ +25° C on full load; De-rate 2W/°C from +25°C to +50°C. Storage & shipping -20° C ~ +65° C
- **Humidity:** 90% on operating and 95% on storage
- **Dielectric Withstand:** Input to frame ground 1800V AC for 1 second
- **Efficiency: 70%** minimum measured at nominal AC main voltage and frequency with maximum loads on all outputs
- **Rise Time:** Less than 20ms on all outputs
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Not exceed 3.5mA
- **MTBF:** 100,000 hours on maximum load at +25° C
- **Dimension (WxHxL):** 150x86x140mm / 6x3.4x5.5inches