

SMX POWER

3005 Avenida Simi, Simi Valley, CA 93063
TEL: (805) 582-2804 FAX: (805) 582-2308
www.smxpower.com



FSP200-50PLA (For Pentium 4) 200 Watts Flex ATX12V Switching Power Supply

Features

- Complied with Flex ATX and ATX12V standard
- Active Power Factor Correction Meeting with EN61000-3-2
- High efficiency and reliability
- Remote On/Off function
- Internal 12V DC fan included
- Noise Killer (Thermal fan speed control function)
- Low noise and ripple
- Complies with FCC part 15 subpart J Class B and CISPR 22 Class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL 1950, CSA C22.2 Level 3, TUV EN60950, NEMKO (CB Report), CE

Input Characteristics

Input Range: 90~264V AC, Full Range Input

Frequency: 47~63Hz

Input Current: 4A (RMS) @115V AC, 2A (RMS) @230V AC

Inrush Current: 50A Max for 115V AC, 80A Max for 230V AC Cold start

Specification

- **Temperature Range:** Operating 0° C ~ +25° C on full load; storage & shipping -20° C ~ +80° C
- **Humidity:** 95% on operating and 95% on storage
- **Dielectric Withstand:** Input to frame ground 1800V AC for 1 second
- **Efficiency:** 68% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise Time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Not exceed 0.75mA at 115V AC, 60Hz
- **MTBF:** 100,000 hours on maximum load at +25° C degree
- **Dimension (WxHxL):** 81.5x40.5x150mm/3.2"x1.6"x6" inches

Output Characteristics

Output Voltage	Minimum Load	Maximum Load	Peak	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.3A	16.0A		± 5%	± 1%	50mV P-P
+5V	0.3A	12.0A		± 5%	± 1%	50mV P-P
+12V	1.5A	12.0A	13A	± 5%	± 1%	120mV P-P
-12V	0.0A	0.8A		± 10%	± 2%	120mV P-P
+5Vsb	0.0A	2.0 A		± 5%	± 1%	100mV P-P

*+5V and +3.3V total output not exceed 61W

*+3.3V, +5V, and +12V total output cannot exceed 180W