

# SMX POWER

3005 Avenida Simi, Simi Valley, CA 93063

TEL: (805) 582-2804 FAX: (805) 582-2308

[www.smxpower.com](http://www.smxpower.com)



## **FSP300-60GLC (With Active PFC)**

**300 Watts ATX12V-2.01, Switching Power Supply**

Meet **Green Power** / **Blue Angel** / **EPA**

### **Features**

- Complied with ATX and ATX12V standard
- Active Power factor correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Remote On/Off function
- Internal 12V DC fan included
- Noise Killer (Thermal fan speed control function)
- Low noise and ripple
- Complies with FCC part 15 subpart J class B and CISPR 22 Class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL60950, CSA C22.2, TUV or VDE, NEMKO (CB Report), IEC60950-1 and CE

### **Input Characteristics**

**Input Range:** 90~265V AC, Full Input Range

**Frequency:** 47~63Hz

**Input Current:** 4A (RMS) @115V AC, 2A (RMS) @230VAC

**Inrush Current:** No damage, typical 100A Max at cold start

### **Output Characteristics**

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.5A	10A	20A	± 5%	± 1%	50mV P-P
+5V	0.3A	10A	20A	± 5%	± 1%	50mV P-P
+12V1DC	1.0A	4A	8A	± 5%	± 1%	120mV P-P
+12V2DC	1.0A	7A	14A	± 5%	± 1%	120mV P-P
-12V	0.0A	0.4 A	0.8 A	± 10%	± 1%	120mV P-P
+5Vsb	0.0A	1.0 A	2.0 A	± 5%	± 1%	50mV P-P

\*+3.3V and +5V total output not exceed 130W

\*Totals output on this subject power supply is 300W.

### **Specification**

- **Temperature Range:** Operating 0° C ~ +50° C on full load; storage & shipping -20° C ~ +80° C
- **Humidity:** 5~95% on operating and storage
- **Dielectric Withstand:** Primary to frame ground 1800V AC for 1 second
- **Efficiency:** min **78%** at 230VAC & **75%** at 115VAC main voltage and frequency with max load on all output.
- **Rise Time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 115V AC/60Hz
- **MTBF:** 100,000 hours on maximum load at +25° C degree
- **Dimension (WxHxL):** 150x86x140mm/5.9"x3.4"x5.5" inches