

# SMX POWER

3005 Avenida Simi, Simi Valley, CA 93063

TEL: (805) 582-2804 FAX: (805) 582-2308

[www.smxpower.com](http://www.smxpower.com)



## **FSP300-60GTB (For Pentium 4 and Athlon XP) 300 Watts ATX12V Switching Power Supply**

### **Features**

- Complied with ATX and ATX12V standard
- Active Power Factor Correction Meeting with EN61000-3-2
- High efficiency and reliability
- Remote On/Off function
- Internal 12V DC 8cm fan included
- Noise Killer (Thermal fan speed control function)
- Low noise and ripple
- Complies with FCC part 15 subpart J Class B and CISPR 22 Class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL 1950, CSA C22.2 Level 3, TUV EN60950, NEMKO EN60950 (CB Report), CE

### **Input Characteristics**

**Input Range:** 90~264V AC, Full Range Input

**Frequency:** 47~63Hz

**Input Current:** 10A (RMS) @ 115V AC, 5A (RMS) @ 230V AC

**Inrush Current:** 60A Max for 264V AC Cold start

### **Output Characteristics**

Output Voltage	Minimum Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.3A	15/28A	± 5%	± 1%	50mV P-P
+5V	1.0A	30/21.5A	± 5%	± 1%	50mV P-P
+12V	0.0A	15.0A	± 5%	± 1%	120mV P-P
-5V	0.0A	0.3A	± 10%	± 2%	100mV P-P
-12V	0.0A	0.8A	± 10%	± 2%	120mV P-P
+5Vsb	0.0A	2.0 A	± 5%	± 1%	50mV P-P

\*+5V and +3.3V total output not exceed 200W

\*When +3.3V is load on 28A, the +5V maximum load is 21.5A

\*When +3.3V is load on 15A, the +5V maximum load is 30A

\*+3.3V, +5V, and +12V total output cannot exceed 280W

### **Specification**

- **Temperature Range:** Operating 0° C ~ +40° C on full load; storage & shipping -20° C ~ +65° C
- **Humidity:** 95% on operating and 95% on storage
- **Dielectric Withstand:** Input to frame ground 1800V AC for 1 second
- **Efficiency:** 60% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise Time:** Less than 20ms on all outputs
- **Hold-up Time:** 16ms minimum at 115V/60Hz; 20ms minimum at 230V/50Hz input voltage
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Not exceed 3.5mA
- **MTBF:** 100,000 hours on maximum load at +25° C degree
- **Dimension (WxHxL):** 150x86 x 140mm/6"x3.4"x5.5" inches