

# SMX POWER

3005 Avenida Simi, Simi Valley, CA 93063

TEL: (805) 582-2804 FAX: (805) 582-2308

[www.smxpower.com](http://www.smxpower.com)



## FSP300-60PLN (For Pentium 4 and Athlon XP) 300 Watts ATX12V Switching Power Supply

### Features

- Complied with ATX and ATX12V standard
- Active Power factor correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Remote On/Off function
- Internal 12V DC fan included
- Noise Killer (Thermal fan speed control function)
- Low noise and ripple
- Complies with FCC part 15 subpart J class B and CISPR 22 Class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL 1950, CSA C22.2 Level 3, TUV EN60950, NEMKO (CB Report), and CE

### Input Characteristics

**Input Range:** 90~264V AC, Full Input Range

**Frequency:** 47~63Hz

**Input Current:** 6A (RMS) @115V AC, 3A (RMS) @230VAC

**Inrush Current:** 60A Max for 115V AC, 90A Max for 230V AC

### Output Characteristics

Output Voltage	Minimum Load	Maximum Load	Peak	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.3A	28A		± 5%	± 1%	50mV P-P
+5V	0.1A	30A		± 5%	± 1%	50mV P-P
+12V	0.0A	15A	18A	± 5%	± 1%	120mV P-P
-5V	0.0A	0.3A		± 5%	± 2%	100mV P-P
-12V	0.0A	0.8 A		± 5%	± 2%	120mV P-P
+5Vsb	0.0A	2.0 A	2.5A	± 5%	± 1%	100mV P-P

\*+5V and +3.3V total output not exceed 180W

\*+3.3V, +5V, and +12V total output not exceed 280W

### Specification

- **Temperature Range:** Operating 0° C ~ +50° C on full load; storage & shipping -20° C ~ +80° C
- **Humidity:** 90% on operating and 95% on storage
- **Dielectric Withstand:** Primary to frame ground 1800V AC for 1 second
- **Efficiency:** 65% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise Time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 0.75mA at 115V AC/60Hz
- **MTBF:** 100,000 hours on maximum load at +25° C degree
- **Dimension (WxHxL):** 150x86x140mm/5.9"x3.4"x5.5" inches